

Product Technical Specifications



CCTV SECURITY CAMERA

SKU #


CESSU-2ACT620CRP-W2.1



GESSU-2ACT620CRP-W2.1

GESS ULTRA™

Outdoor Dome Camera



1080p resolution



Weather proof



Vandal Resistant

MAIN FEATURES

- 1/2.7" 2MP CMOS
- AGC, AWB, AES
- 2/3DNR,D-WDR, Lens Rectification
- Multi Languages OSD Control from Recorder
HD CVI /HD TVI/ AHD/ CVBS Output Selectable from Dip Switch
- DC12V

RECOMMENDED USE



This product is ideal for:

- Applications that require the camera to be mounted at normal installation heights.
Recommended installation height 8-12 Feet.
- Used for wide area coverage.

IP 66

Totally protected against dust and water projected in powerful jets (12.5mm nozzle) against the enclosure from any direction shall have no harmful effects.

RECOMMENDED USE





TECHNICAL SPECIFICATIONS

SKU #

GESSU-2ACT620CRP-W2.1

Image Sensor	1/2.7" 2MP CMOS
Signal System	NTSC/PAL
Effective Pixels	1958(H) x 1105(V)
Min. Illumination	0 lux(IR ON)
Synchronization	Internal synchronization
Video Output	"CVI,TVI,AHD(1080P@25fps,1080P@30fps) Analog(1280x576,1280x480)"
S/N Ratio	41dB(AGC OFF)
NR	2/3DNR
Shutter	Auto
Day&Night	Smart/Color/B&W
White Balance	Auto/Manual
OSD	English/Chinese/Spanish/Italian/Traditional Chinese
AGC	Auto
IR LED	12pcs High Power IR LED
Lens	2.1mm (140°View Angle)
IR Range	25m
Power Supply	DC12V±10%
Power Consumption	<4W
Weight	320g
IP Rating	IP66
Storage Temperature	-20°C ~60°C
Working Temperature/Humidity	-10°C ~60°C, Humidity 90% or less (non-condensing)

www.gess-inc.com info@gess-in.com

USA | PUERTO RICO | COLOMBIA



GESS[®]
TECHNOLOGIES